The Wall


IWA Series

The Wall. Make a bold statement.




Realize the full potential of The Wall.

Innovation doesn't rest. It is a relentless pursuit to create unrivaled experiences. An ambition to inspire others with greatness. This unending quest has culminated in Samsung pushing the boundaries of innovation yet again. Based on a rich heritage of R&D and accumulated expertise, the potential of The Wall can now be fully realized. A display that transforms the existing concept of LED screen. A display that goes beyond anything else available in the market today. The Wall makes a bold, breathtaking statement like no other. The possibilities are endless. And its potential is limitless.




Accurate Picture Quality

- Deeper black color and contrast
- Vivid, vibrant color purity
- Accurate color mapping and grayscale expression




Optimal Picture Quality

- AI optimized visuals
- Advanced picture refinement and dynamic range
- Smooth, judder-free visuals



Enhanced Installation

- Pre-adjusted seam between modules
- Simple, cable-free connection




Flexible Design

• Multiple installation options for any location



Proven Safety

- Blue light eye protection
- Electromagnetic wave minimization



Advanced Usability

- Flicker-free visuals with screen synchronization
- Simple 8K playback with just one box
- \bullet View up to four sources on one screen



Key features



Black Seal Technology

An abyss of depth

A deep black background blankets the screen with perfect uniformity, creating a seamless canvas for purer black levels with enhanced depth that delivers unparalleled contrast and immaculate detail.



Ultra Chroma Technology

Superior color purity

Colors leap to life with spectacular vibrancy to recreate scenes as if you were there in real life. Narrower wavelengths produce RGB colors two times purer* and more accurate than conventional LEDs.

* Figure is based on internal testing standards against Samsung's conventional LED Signage.



20bit Processing

Colors mapped to perfection

The Wall's 20bit processing presents exact color mapping with faultless accuracy. Deeper bit depth at low greyscale also delivers extraordinary contrast ratio and smooth, natural tonal gradients.



Linear Grayscale

Continuous natural shading

A precise linear grayscale showcases intricacies in every scene, naturally delivering textures, volume and shades. The elevated continuity pulls you further into your content for unbroken immersion.

Key features



MICRO AI Processor

Instant AI optimization

Every second of content is instantly analyzed and optimized for perfect picture quality. The powerful AI processor delivers superior visuals in any size up to 8K resolution, enhancing contrast and removing noise.



MICRO HDR

Dazzling dynamic range

Reimagine the limits of conventional screens with advanced picture refinement—HDR10/10+ and LED HDR—to illuminate ideal peak brightness and contrast in every scene for precise, true-to-life imagery.



MICRO Motion

Smooth, seamless motion

The Wall automatically converts standard 60Hz signals to 120Hz, removing motion judder in fast-paced action for smoother streams and a seamless viewing experience, every time.



Factory Seam Adjustment

Installation reimagined

Installation is transformed by eliminating module-by-module seam adjustment. Now installers adjust only per cabinet, saving time while improving mechanical quality for immersive viewing.



Docking Connection

Connection without cables

The Wall enables simple and easy installation with a cable-less design. Minimal signal or power cable connections are required between cabinets, even in the event of any module repair service.

Key features



Endless Design

No Compromise creations

Design buildouts to your exact specifications thanks to The Wall's endless installation possibilities. Hang from walls and ceilings, curve around pillars or angle from edges. The choice is yours.



Proven Safety

Certified safety, maximum protection

Keep eyes comfortable and safe with TUV Rheinland Eye Comfort Certification, minimizing harmful blue light, while EMC Class B certification minimizes electromagnetic waves for advanced protection.



Simple 8K Playback

Powerful 8K playback with just one box

The Wall enables 8K content playback with just one S-Box, as well as 16K content playback horizontally with the new and improved S-Box performance, delivering more pixels with enhanced precision.



On-Air Functionality

Expertly engineered for any studio setting

The Wall is built for any studio environment, ensuring screen synchronization and supporting an industry top level 7,680 Hz refresh rate. Plus, the refresh rate can be adjusted based on camera frequency, minimizing flicker lines.



Multi View

Simultaneous source experience

With Multi View, The Wall enables simultaneous multi-source playback from up to four sources, all on one screen, without any additional splitter required for dynamic content display.

Specifications

		IWA		
	Model	IW008A IW012A IW016A		
		LH008IWAMWS	LH012IWAMWS	LH016IWAMWS
Physical Parameter	Pixel Pitch	0.84 mm	1.26 mm	1.68 mm
	Pixel Configuration	1 red,1 green,1 blue	1 red, 1 green, 1 blue	1 red, 1 green, 1 blue
	Configuration (LxH, per cabinet)	960 x 540 pixels	640 x 360 pixels	480 x 270 pixels
	Diode Type	Flip-chip RGB LED	Flip-chip RGB LED	Flip-chip RGB LED
	Dimensions (mm, LxHxD, per cabinet)	806.4 x 453.6 x 36.5 mm	806.4 x 453.6 x 36.5 mm	806.4 x 453.6 x 36.5 mm
	Dimensions (inch, per cabinet)	36.4 x 1.4 inch	36.4 x 1.4 inch	36.4 x 1.4 inch
	No. of Modules (WxH, per cabinet)	4 x 3	4 x 3	4 x 3
	Weight (per cabinet/per m²)	11.2 kg / 30.6 kg	11.2 kg / 30.6 kg	11.2 kg / 30.6 kg
Optical Parameter	Brightness (Peak/Max) (1)	1,600 nit / 500 nit	1,600 nit / 800 nit	1,400 nit / 1,000 nit
	Contrast Ratio (2)	24,000 : 1	24,000:1	21,000 : 1
	HDR Compatibility	LED HDR / HDR10+ support / Al Picture	LED HDR / HDR10+ support / Al Picture	LED HDR / HDR10+ support / Al Picture
	Viewing Angle - Horizontal	170°	170°	170°
	Viewing Angle - Vertical	155°	155°	155°
	Bit Depth	16 bit (Internal processing 20bit)	16 bit (Internal processing 20bit)	16 bit (Internal processing 20bit)
	Color Temperature - Default	6,500K ± 500K (Floating bin)	6,500K ± 500K (Floating bin)	6,500K ± 500K (Floating bin)
	Color Temperature - Adjustable	2,800K ~ 10,000K (using S-Box)	2,800K ~ 10,000K (using S-Box)	2,800K ~ 10,000K (using S-Box)
	Video Rate	100/120 Hz	100/120 Hz	100/120 Hz
Electrical Parameter	Input Power Range	100 ~ 240 VAC, 50/60 Hz	100 ~ 240 VAC, 50/60 Hz	100 ~ 240 VAC, 50/60 Hz
	Power Consumption - Max	383 (W/m²) /140 (W/Cabinet)	383 (W/m²) /140 (W/Cabinet)	411 (W/m²) / 150 (W/Cabinet)
	Power Consumption - Typ	260 (W/m²) / 95 (W/Cabinet)	233 (W/m²) / 85 (W/Cabinet)	225 (W/m²) / 82 (W/Cabinet)
	Heat Generation - Max	1,307 (BTU/m²) / 478 (BTU/Cabinet)	1,307 (BTU/m²) / 478 (BTU/Cabinet)	1,400 (BTU/m²) / 512 (BTU/Cabinet)
	Heat Generation - Typ	887 (BTU/m²) / 324 (BTU/Cabinet)	794 (BTU/m²) / 291 (BTU/Cabinet)	766 (BTU/m²) / 280 (BTU/Cabinet)
	Refresh Rate (3)	11,520 Hz	11,520 Hz	15,360 Hz
	Power Redundancy	Yes	Yes	Yes
Operational Parameter	Working Temperature / Humidity	0°C~+40°C /10%~80%RH	0°C~+40°C /10%~80%RH	0°C~+40°C /10%~80%RH
	Storage Temperature / Humidity	-20°C~+45°C / 5%~95%RH	-20°C~+45°C / 5%~95%RH	-20°C~+45°C / 5%~95%RH
	IP Rating	IP20	IP20	IP20
	LED Lifetime	150,000 hours	150,000 hours	150,000 hours
	Controller	SNOW-AAE	SNOW-AAE	SNOW-AAE
Connectivity	Connectivity	Optical * HDBT is used for connecting only BT/Wifi module	Optical * HDBT is used for connecting only BT/Wiff module	Optical ** HDBT is used for connecting only BT/Wifi module
Certification	Safety	62368-1, 60950-1	62368-1, 60950-1	62368-1, 60950-1
	EMC	Class B	Class B	Class B
	Eye-protection	TUV Eye Comfort	TUV Eye Comfort	TUV Eye Comfort
	Fire-protection	N/A	N/A	N/A
Service	Service	Front	Front	Front
	Operating System	Tizen 6.0	Tizen 6.0	Tizen 6.0
Features	MagicINFO	Yes	Yes	Yes
	Sensor	Temperature	Temperature	Temperature
	Other	Eco Image Enhancer, 3D mode	Eco Image Enhancer, 3D mode	Eco Image Enhancer, 3D mode
	Smart TV type	-	-	-
	Smart Function	Multiview, Screen-mirroring	Multiview, Screen-mirroring	Multiview, Screen-mirroring
	Bixby Language	-	-	-
Accessories	Accessories	Décor Frame (Standard), Frame Kit	Décor Frame (Standard), Frame Kit	Décor Frame (Standard), Frame Kit
	Remote Control	-	- Coor Frame (Standard), Frame Nit	- Decorrame (Standard), Frame Nit
Package	Box Dimension (mm, WxHxD)	927 x 161 x 592 mm	927 x 161 x 592 mm	927 x 161 x 592 mm
	Package Weight (per cabinet)	927 x 101 x 592 IIIII	927 x 161 x 392 IIIII	927 X 161 X 592 IIIII
	Curve	Concave(6000R), Convex(6000R), L-type	Concave(6000R), Convex(6000R), L-type	Concave(6000R), Convex(6000R), L-typ
Special Installation		Forward, Ceiling	Forward, Ceiling	Forward, Ceiling
	Inclination	i oi waru, Ceiting	-	Forward, Ceiting
nstallation	Rotation	N/A	N/A	N/A

⁽¹⁾ Peak value according to IDMS (Information Display Measurement Standard) (2) Measured under 10 lux light. Contrast in darkroom exceeds 1000000:1 (3) Referring to visual refresh rate

SAMSUNG

About Samsung Electronics Co., Ltd.

Samsung Electronics Co., Ltd. inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, cameras, digital appliances, medical equipment, network systems, and semiconductor and LED solutions. For the latest news, please visit the Samsung Newsroom at news.samsung.com.

LED Signage

For more information about Samsung The Wall, visit www.samsung.com/business or www.samsung.com/displaysolutions

Copyright © 2021 Samsung Electronics Co. Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co. Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd. 416, Maetan 3-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 443-772, Korea